



nev L2C.6



60 VOLT WITH AC SYSTEM

AGM OR LITHIUM BATTERIES

155/65 R13 STEEL RIMS
WITH WHEEL COVERS

LED LIGHTS WITH DRL
FUNCTION

HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE

ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO)
Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com



nev L2C.6



ITALCAR is an Italian brand

places:	2
batteries:	AGM ou LITHIUM
motor:	AC – 60V
controller:	AC – 450A
transmission:	rear axle, ratio 12,49:1
steering:	self compensating single reduction rack and pignon
performances:	
max speed:	45 km/h (L7e)
range:	80km (AGM) – 110km (LITHIUM)
max hill climbing ability:	20% (then 11°)
dimensions:	
overall (LxWxH)	3300mm x 1400mm x 1670mm
dimensions:	
cargo (LxWxH)	1500mm x 1300mm x 265mm
ground clearance (empty):	200mm
turning radius:	6 mt
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel with hand brake
front	disc
rear	drum
tires:	155 / 65 – 13
recommended pressure:	2,5 bar (25kPa)
battery charger:	included
basic configuration:	open “T-shape” doors, roll-bar with 3-point safety belts, laminated glass windscreen, front and rear lights and direction indicators, side and central mirrors, glove compartment and rear electric tipper box, radio, USB charging slot, air conditioning
optional:	whole doors (closed cabin)

* average autonomy measured on a flat road @ constant speed of 20km/h

all above specification were correct at the time of the publishing and are indicatives and not binding. ITALCAR INDUSTRIAL Srl maintains the right to bring any changes without notice

seguici su - follow us on



clicca mi piace - like us on

